



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 155.00 lm/W			
MODEL	ZGSM-SDD60H6	I _{max} (cd)	3855	η street_up(%)	0.0
NOMINAL POWER(W)	60	LOR(%)	100.0	η street_down(%)	50.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	9300	η house_up(%)	0.0
NOMINAL FLUX(lm)	9300	MAXIMUM @(C,γ)	180,35.0	η house_down(%)	49.5
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	18.838




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:



Classification:


IES:Type V - Very Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:8.042cd/klm
 Max.At90:0cd/klm
 Max.80-90:8.042cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	3855
90%	3470
80%	3084
70%	2699
60%	2313
50%	1928
40%	1542
30%	1157
20%	771
10%	386
5%	193

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	lum, lamp
10	3559	3541	3531	3520	3572	3533	3502	3488	0- 10	336.5	336.5	3.62,3.62
20	3529	3541	3564	3543	3579	3524	3487	3456	10- 20	997.7	1334	14.3,14.3
30	3584	3668	3756	3734	3767	3676	3592	3519	20- 30	1653	2987	32.1,32.1
40	3623	3641	3627	3645	3687	3640	3558	3552	30- 40	2325	5312	57.1,57.1
50	2494	2456	2459	2451	2497	2415	2408	2431	40- 50	2418	7731	83.1,83.1
60	303.5	370.7	411.5	415.0	351.1	321.1	318.2	334.8	50- 60	1212	8942	96.2,96.2
70	117.3	148.9	137.1	145.0	133.4	135.9	123.4	139.2	60- 70	215.0	9157	98.5,98.5
80	53.23	67.17	70.73	69.00	53.81	67.71	67.93	65.73	70- 80	98.85	9256	99.5,99.5
90	0	0	0	0	0	0	0	0	80- 90	43.94	9300	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.480m [K=1.0000]
 Remarks:

LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	1503.1	16.2
FM - Front-Medium(30-60)	3007.5	32.3
FH - Front-High(60-80)	163.24	1.8
FVH - Front-Very High(80-90)	22.057	0.2
Total Forward Light	4695.9	50.5

BL - Back-Low(0-30)	1484	16.0
BM - Back-Medium(30-60)	2947.8	31.7
BH - Back-High(60-80)	150.62	1.6
BVH - Back-Very High(80-90)	21.88	0.2
Total Back Light	4604.3	49.5

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B3-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	4604.3	0	4604.3
Street Side	4695.9	0	4695.9


C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:2.3kg
SPEC.:	DIM.: 166*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*70 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```